CORESHIELDTM MICRO-FOAM NITRILE COATING

Having the right gloves for the right application is crucial to providing your workers with optimum protection.

Thanks to its high-performance fiber, the Honeywell CoreShield™ range of 22 styles offers complete cut protection from level A/A1 to F/A9, in a choice of 4 various gauges (from 10gg to 18gg) and 3 different coatings.

With CoreShield™, simplified hand protection is at your fingertips.



CoreShield[™] — — ■ ■ ■ Cut protection made simple

INDUSTRIES

Manufacturing, Automotive, Metal stamping, Glass handling, Construction, Logistics

APPLICATIONS

Please refer to CoreShield™ Selector Guide to choose your Honeywell CoreShield™ gloves

FEATURES AND BENEFITS



EASY TO CHOOSE

The color-coded marking system makes it easy for you to choose the gloves you need for your application, according to the new EN 388:2016 European standard and ANSI-105-2016 American standard. Choose by level of cut protection, grip, dexterity and fit.



EASY TO WEAR

One of the lightest-weight cutprotective gloves on the market, they help to prevent hand fatigue for workers who need to wear them all day long.

Skin-friendly yarns that reduce the allergy risk to wearers. CoreShield $^{\text{M}}$ gloves are certified STANDARD 100 by OEKO-TEX $^{\text{@}}$.

Hand and wrist protection.

Touchscreen resistive and capacitive.



COST-EFFECTIVE TO BUY

Thumb reinforcement.


CoreShield™ High Performance Coating has special abrasion technology for x2 durability coating.

The washability of the glove material means that even after 5 washing cycles, there are no significant changes in performance or size.

CoreShield™ gloves have a longer life, which in turn translates into less frequent replacements and reduced cost of ownership. Purchasing of CoreShield™ gloves is an investment.







CoreShield™ High Performance
Micro-Foam Nitrile coating provides
360° breathability, excellent grip
performance, water and oil proof coating,
abrasion resistance, reduced hand fatigue
and excellent dexterity.



CoreShield™ Engineered Yarn
Skin friendly and comfortable material to shield the cut resistant material
Softer skin-friendly yarn in contact with the skin

CORESHIELD™ CHOOSE YOUR MICRO-FOAM COATING

SKU	PRODUCT NAME & DESCRIPTION	CUT LEVEL & COLOR CODING	EN388:2016 PERFORMANCES	ANSI/ISEA 105:2016 PERFORMANCES		EN407
				CUT	ABRASION	PERFOR- MANCES
21-1515B	CoreShield, 15 gauge nylon black liner, nitrile micro-foam black coating, A1/A	A1 A	4X31A	A1	6	
21-1518B	CoreShield, 18 gauge nylon black liner, nitrile micro-foam black coating, A1/A	A1 A	4X21A	A1	6	
22-7513B	CoreShield, 13 gauge HPPE black liner, nitrile micro-foam black coating, A2/B	A2 B	4X42B	A2	6	
22-7513W	CoreShield, 13 gauge HPPE white liner, nitrile micro-foam grey coating, A2/B	A2 B	4X42B	A2	6	
22-7518B	CoreShield, 18 gauge HPPE grey liner, nitrile micro-foam black coating, A2/B	A2 B	4X31B	A 2	6	
23-0513B	CoreShield, 13 gauge HPPE/basalt black liner, nitrile micro-foam black coating, A3/C	A3 C	4X43C	А3	6	X1XXXX
23-7518B	CoreShield, 18 gauge HPPE/basalt black liner, nitrile micro-foam black coating A3/C	A3 C	4X42C	А3	6	X1XXXX
24-0513B	CoreShield, 13 gauge HPPE/basalt black liner, nitrile micro-foam black coating, A4/D	A4 D	4X43D	Α4	6	
24-0513W	CoreShield, 13 gauge HPPE/basalt white liner, nitrile micro-foam grey coating, A4/D	A4 D	4X43D	Α4	6	
24-9518B	CoreShield, 18 gauge, HPPE/steel black liner, nitrile micro-foam black coating, A4/D	A4 D	4X31D	Α4	6	
25-0513B	$Core Shield, 13\ gauge\ HPPE/stainless\ steel\ black\ liner,\ nitrile\ micro-foam\ black\ coating,\ A5/E$	A5 E	4X42E	A5	6	
26-0513W	CoreShield, 13 gauge HPPE/alloy/basalt white liner, nitrile micro-foam grey coating, A6/F	A6 F	4X44F	A6	6	
26-0513B	CoreShield, 13 gauge HPPE/alloy/basalt black liner, nitrile micro-foam black coating, A6/F	A6 F	4X44F	A6	6	
27-0513B	CoreShield, 13 gauge HPPE/alloy black liner, nitrile micro-foam coating, A7/F	A7 F	4X44F	Α7	6	

Washing instructions

Maximum washing temperature 30°C/86°F mild process

X Do not bleach

Tumble dry possible at low temperature, exhaust temperature max. 60°C/140°F

➢ Do not iron

Do not dry clean

Packaging: Gloves are packed in a plastic bag by inner pack of 10 pairs, 10 inner packs per case (100 pairs). Sizes: from 6/XS to 11/XXL

Honeywell Safety Products UK Limited

Edison Rd – Basingstoke RG21 6QD United Kingdom Phone: +44 (0) 1256 693 200 info-uk.hsp@honeywell.com

Honeywell Safety Products Europe SAS

Immeuble Edison Paris Nord 2 33, rue des Vanesses – CS 55288 Villepinte 95958 Roissy CDG Cedex – France +33 (0) 1 49 90 79 79 info-export.hsp@honeywell.com

Industrial Safety PPE Technical Support

Free Phone: 00 800 3344 2803 (free calls in Europe) Phone: +44 (0) 1698 647 087 (paid calls) IS.PPE.TECHSUPPORT.EUROPE@honeywell.com

www.honeywellsafety.com

THE FUTURE IS WHAT WE MAKE IT

